

SIMONA® PE Platten, kompakt, extrudiert

DIN EN ISO 14632			
Dicke	Toleranz min.	Toleranz max.	Toleranz
mm	mm	mm	mm
0,50	0,40	0,60	+/- 0,10
1,00	0,89	1,11	+/- 0,11
1,50	1,38	1,62	+/- 0,12
2,00	1,86	2,14	+/- 0,14
3,00	2,83	3,17	+/- 0,17
4,00	3,80	4,20	+/- 0,20
5,00	4,77	5,23	+/- 0,23
6,00	5,74	6,26	+/- 0,26
8,00	7,68	8,32	+/- 0,32
10,00	9,62	10,38	+/- 0,38
12,00	11,56	12,44	+/- 0,44
15,00	14,47	15,53	+/- 0,53
20,00	19,32	20,68	+/- 0,68
25,00	24,17	25,83	+/- 0,83
30,00	29,02	30,98	+/- 0,98
35,00	33,87	36,13	+/- 1,13
40,00	38,72	41,28	+/- 1,28
50,00	48,42	51,58	+/- 1,58

SIMONA® PE Platten, kompakt, extrudiert

Länge / Breite		DIN EN ISO 14632			
von	bis	Länge min.	Länge max.	Breite min.	Breite max.
mm	mm	mm	mm	mm	mm
0	≤ 500	- 1,0	+ 2,0	- 1,0	+ 2,0
> 500	1.000	- 1,0	+ 3,0	- 1,0	+ 3,0
> 1.000	1.500	- 1,0	+ 4,0	- 1,0	+ 4,0
> 1.500	2.000	- 1,0	+ 6,0	- 1,0	+ 4,0
> 2.000	3.000	- 1,0	+ 8,0	- 1,0	+ 6,0
> 3.000	4.000	- 1,0	+ 11,0	- 1,0	+ 7,0

SIMONA® PP Platten, kompakt, extrudiert

DIN EN ISO 15013			
Dicke	Toleranz min.	Toleranz max.	Toleranz
mm	mm	mm	mm
0,50	0,40	0,60	+/- 0,10
1,00	0,89	1,11	+/- 0,11
1,50	1,38	1,62	+/- 0,12
2,00	1,86	2,14	+/- 0,14
3,00	2,83	3,17	+/- 0,17
4,00	3,80	4,20	+/- 0,20
5,00	4,77	5,23	+/- 0,23
6,00	5,74	6,26	+/- 0,26
8,00	7,68	8,32	+/- 0,32
10,00	9,62	10,38	+/- 0,38
12,00	11,56	12,44	+/- 0,44
15,00	14,47	15,53	+/- 0,53
20,00	19,32	20,68	+/- 0,68
25,00	24,17	25,83	+/- 0,83
30,00	29,02	30,98	+/- 0,98
35,00	33,87	36,13	+/- 1,13
40,00	38,72	41,28	+/- 1,28
50,00	48,42	51,58	+/- 1,58

SIMONA® PP Platten, kompakt, extrudiert

Länge / Breite		DIN EN ISO 15013			
von	bis	Länge min.	Länge max.	Breite min.	Breite max.
mm	mm	mm	mm	mm	mm
0	≤ 500	- 1,0	+ 2,0	- 1,0	+ 2,0
> 500	1.000	- 1,0	+ 3,0	- 1,0	+ 3,0
> 1.000	1.500	- 1,0	+ 4,0	- 1,0	+ 4,0
> 1.500	2.000	- 1,0	+ 6,0	- 1,0	+ 4,0
> 2.000	3.000	- 1,0	+ 8,0	- 1,0	+ 6,0
> 3.000	4.000	- 1,0	+ 11,0	- 1,0	+ 7,0

SIMONA® PVC Platten, kompakt, extrudiert

DIN EN ISO 11833-1			
Dicke	Toleranz min.	Toleranz max.	Toleranz
mm	mm	mm	mm
0,50	0,39	0,61	+/- 0,11
1,00	0,87	1,13	+/- 0,13
1,50	1,36	1,64	+/- 0,14
2,00	1,84	2,16	+/- 0,16
3,00	2,81	3,19	+/- 0,19
4,00	3,78	4,22	+/- 0,22
5,00	4,75	5,25	+/- 0,25
6,00	5,72	6,28	+/- 0,28
8,00	7,66	8,34	+/- 0,34
10,00	9,60	10,40	+/- 0,40
12,00	11,54	12,46	+/- 0,46
15,00	14,45	15,55	+/- 0,55
20,00	19,30	20,70	+/- 0,70
25,00	24,15	25,85	+/- 0,85
30,00	29,00	31,00	+/- 1,00
35,00	33,85	36,15	+/- 1,15
40,00	38,70	41,30	+/- 1,30
50,00	48,40	51,60	+/- 1,60

SIMONA® PVC Platten, kompakt, extrudiert

Länge / Breite		DIN EN ISO 11833-1			
von	bis	Länge min.	Länge max.	Breite min.	Breite max.
mm	mm	mm	mm	mm	mm
0	≤ 500	- 0	+ 3,0	- 0	+ 3,0
> 500	1.000	- 0	+ 4,0	- 0	+ 4,0
> 1.000	1.500	- 0	+ 5,0	- 0	+ 5,0
> 1.500	2.000	- 0	+ 6,0	- 0	+ 6,0
> 2.000	4.000	- 0	+ 7,0	- 0	+ 7,0

SIMONA® PVDF Platten, kompakt, extrudiert

Dicke	ISO 15014		
	Toleranz min.	Toleranz max.	Toleranz
mm	mm	mm	mm
1,00	0,89	1,11	+/- 0,11
2,00	1,86	2,14	+/- 0,14
3,00	2,83	3,17	+/- 0,17
4,00	3,80	4,20	+/- 0,20
5,00	4,77	5,23	+/- 0,23
6,00	5,74	6,26	+/- 0,26
8,00	7,68	8,32	+/- 0,32
10,00	9,62	10,38	+/- 0,38
12,00	11,56	12,44	+/- 0,44
15,00	14,47	15,53	+/- 0,53
20,00	19,32	20,68	+/- 0,68

SIMONA® PVDF Platten, kompakt, extrudiert

Länge / Breite		ISO 15014			
von	bis	Länge min.	Länge max.	Breite min.	Breite max.
mm	mm	mm	mm	mm	mm
0	≤ 500	- 1,0	+ 2,0	- 1,0	+ 2,0
> 500	1.000	- 1,0	+ 3,0	- 1,0	+ 3,0
> 1.000	1.500	- 1,0	+ 4,0	- 1,0	+ 4,0
> 1.500	2.000	- 1,0	+ 6,0	- 1,0	+ 4,0
> 2.000	3.000	- 1,0	+ 8,0	- 1,0	+ 6,0
> 3.000	4.000	- 1,0	+ 11,0	- 1,0	+ 7,0

SIMOLUX (PETG) Platten, kompakt, extrudiert

Dicke	SIMONA		
	min. Tol.	max. Tol.	Toleranz
mm	mm	mm	mm
1,00	0,89	1,11	+/- 0,11
1,50	1,38	1,62	+/- 0,12
2,00	1,80	2,20	+/- 0,20
3,00	2,76	3,06	+ 0,06 / - 0,24
4,00	3,76	4,06	+ 0,06 / - 0,24
5,00	4,71	5,07	+ 0,07 / - 0,29
6,00	5,71	6,07	+ 0,07 / - 0,29
8,00	7,68	8,08	+ 0,08 / - 0,32
10,00	9,65	10,09	+ 0,09 / - 0,35
12,00	11,60	12,10	+ 0,10 / - 0,40
15,00	14,52	15,12	+ 0,12 / - 0,48
20,00	19,52	20,12	+ 0,12 / - 0,48

SIMOLUX (PETG) Platten, kompakt, extrudiert

Länge / Breite		SIMONA			
von	bis	Länge min.	Länge max.	Breite min.	Breite max.
mm	mm	mm	mm	mm	mm
0	≤ 500	- 0	+ 3,0	- 0	+ 2,5
> 500	1.000	- 0	+ 4,0	- 0	+ 3,0
> 1.000	1.500	- 0	+ 5,0	- 0	+ 3,5
> 1.500	2.000	- 0	+ 6,0	- 0	+ 4,0
> 2.000	3.050	- 0	+ 7,0		
> 3.050		- 0	+ 0,5%		

SIMOLIFE EVA flex & superflex Platten, kompakt, extrudiert

Dicke	in Anlehnung an DIN EN ISO 15013		
	Toleranz min.	Toleranz max.	Toleranz
mm	mm	mm	mm
0,50	0,40	0,60	+/- 0,10
1,00	0,89	1,11	+/- 0,11
1,50	1,38	1,62	+/- 0,12
2,00	1,86	2,14	+/- 0,14
3,00	2,83	3,17	+/- 0,17
4,00	3,80	4,20	+/- 0,20
5,00	4,77	5,23	+/- 0,23
6,00	5,74	6,26	+/- 0,26
8,00	7,68	8,32	+/- 0,32
10,00	9,62	10,38	+/- 0,38
12,00	11,56	12,44	+/- 0,44
15,00	14,47	15,47	+/- 0,53
20,00	19,32	20,68	+/- 0,68

SIMOLIFE EVA flex & superflex Platten, kompakt, extrudiert

Länge / Breite		in Anlehnung an DIN EN ISO 15013			
von	bis	Länge min.	Länge max.	Breite min.	Breite max.
mm	mm	mm	mm	mm	mm
0	≤ 500	- 1,0	+ 2,0	- 1,0	+ 2,0
> 500	1.000	- 1,0	+ 3,0	- 1,0	+ 3,0
> 1.000	1.500	- 1,0	+ 4,0	- 1,0	+ 4,0
> 1.500	2.000	- 1,0	+ 6,0	- 1,0	+ 4,0
> 2.000	3.000	- 1,0	+ 8,0	- 1,0	+ 6,0
> 3.000	4.000	- 1,0	+ 11,0	- 1,0	+ 7,0